

# Wacker Neuson 25 kw Diesel Generator Towable

Description	Metric	Imperial
Length x width x height (skid mounted)	1946 x 889 x 1384mm	76.6 x 35 x 54.5in
Operating weight, Skid mounted	1372kg	3026lb
Dry weight, Skid mounted	950kg	2094lb
Generator with optional trailer Length x width x height	4064 x 1715 x 2032mm	160 x 67.5 x 80in
Operating weight with optional trailer	1771kg	3906lb
Dry weight with optional trailer	1349kg	2974lb
Standby output	20.4 / 25.5kW/kVA	20.4 / 25.5kW/kVA
Prime output	19.5 / 24.4kW/kVA	19.5 / 24.4kW/kVA
AC voltage 1 Ø	120, 127, 139, 240, 254, 277V	120, 127, 139, 240, 254, 277V
AC voltage 3 Ø	208, 220, 240, 416, 440, 480V	208, 220, 240, 416, 440, 480V
Frequency	60Hz	60Hz
Power factor (1 phs / 3 phs)	1.0 / 0.8	1.0 / 0.8
Sound level	65dB(A)	65dB(A)
AC receptacles 1 Ø 120V - 20 amp GFI duplex	2	2
AC receptacles 1 Ø 120/240V - 50 amp twist lock	1	1
AC receptacles 1 Ø 120/240V - 30 amp twist lock	1	1
Engine Type	Isuzu 2.2 L	
Displacement	2179cm <sup>3</sup>	133in <sup>3</sup>
Max. Rated Power at	26.4 kW at 1800 rpm	35.4 hp at 1800 rpm
Rated Speed*		
Power Rating Specification	SAE J1995, ISO 8528-1	SAE J1995, ISO 8528-1
Battery	12V/750CCA	12V/750CCA
Voltage regulation no load to full load	+/-1%	+/-1%
Voltage regulation steady state	+/-0.2%	+/-0.2%
Insulation class	H	H
Generator type	Brushless w/ AVR	Brushless w/ AVR
Fuel consumption (full load) with / without generator	6.8l/h	1.8US gal/h
Fuel tank capacity	490l	129.4US gal
Run time	100% - 77.2h	100% - 77.2h
Trailer hitch type	3" Pintle	3" Pintle